

19.5", 21.5", and 23.6" Analog HD over Coax LED Security Monitor

Feature

- ★ 19.5", 21.5", and 23.6" HD LED Security Video Monitor
- ★ True HD Digital (HDMI) & **HD Analog (BNC)** Video Inputs
- ★ 1x HDMI Input, 2x HD BNC Inputs, and **2x HD BNC Outputs**
- ★ Support HD-TVI, HD-AHD, HD-CVI, and CVBS
- ★ Support up to 5MP HD-TVI, 5MP HD-AHD, and 4MP HD-CVI
- ★ CE, RoHS, and FCC-DOC
- ★ 24/7 and 50,000 Hour Rated Lifespan
- ★ 1 Years Warranty



Specification

Part Number	APHD195	APHD215	APHD236
Panel Type	19.5", 16:9 LED Panel	21.5", 16:9 LED Panel	23.6", 16:9 LED Panel
Case Type	Plastic		
Pixel Count	1920(H) x 1080(V)		
TV Lines	1000 Lines		
Brightness	250cd/m2		
Contrast Ratio	1000:1		
Response Time	5ms		
Display Colors	16.7M		
Viewing Angle	178/178 (H/V)		
Video Inputs	2 x HD Analog (TVI/AHD/CVI), 1x HDMI		
Video Outputs	2 x HD Analog (TVI/AHD/CVI)		
HDMI Format	2560x1440@30/60, 1920x1080@25/30/50/60HZ, 1600x1200@60HZ 1440x900@60HZ, 1366x768@60HZ, 1280x1024@60HZ 1280x720@60HZ, 1024x768@60HZ, 800x600@60HZ		
Analog HD	TVI: 5MP@20fps, 4MP@25fps, 3MP@18.75fps, 2560x1440@25/30fps, 1080P@25/30fps, 720P@25/30fps		
	AHD: 5MP@20fps, 4MP@25fps, 2560x1440@25/30fps, 1080P@25/30fps, 720P@25/30fps		
	CVI: 4MP@25fps 2560x1440@25/30fps, 1080P@25/30fps, 720P@25/30/50/60fps		
Power Consumption	12VDC, 3A, <18W	12VDC, 3A, <21W	12VDC, 3A, <25W
VESA Mounting	100mm x 100mm		
Auto Adjustment	Yes		
OSD Menu	Yes		
Working Temperature	0 ~ 40°C		
Work Humidity	5% - 90%		
OSD Language	English, Spanish, Italian, German, French, Polish, Russia, Dutch, and Danish		
Video Compatibility	NTSC/PAL		
Accessories	Power Cord, Adapter, Stand, User's Guide, HDMI Cable		
Packing Dimensions	530 x 120 x 420mm 20.8" x 4.7" x 16.5"	580 x 120 x 440mm 22.8" x 4.7" x 17"	580 x 120 x 440mm 22.8" x 4.7" x 17"
Gross Weight	4.3KG / 9.5lb	4.5KG / 9.9lb	6.3KG / 13.9lb
Safety & EMC Certification	FCC-DOC, CE, and RoHS		

Connectors



Dimension

