

DS-2TP21B-6AVF/W

Body Temperature Measurement Camera



- 160 x 120 Resolution (Thermal), and 8 MP Resolution (Optical)
- Thermographic Accuracy up to $\pm 0.9^{\circ}$ F ($\pm 0.5^{\circ}$ C)
- Display Fusion of Thermal View and Optical View
- 640 × 480 Resolution 3.5" LCD Touch Display
- Supports Live View on PC, Mobile Device, or External Monitor
- Supports Audio Intercom
- Supports Color Highlight Alarm and Audio Alarm

The Hikvision DS-2TP21B-6AVF/W handheld thermal camera is specially designed for body temperature measurement. It's equipped with a 160×120 resolution thermal detector. It is capable of discovering and tracking people with elevated body temperatures in crowded public areas and can be widely used in places such as customs, airport, schools, and hospitals for inspection and quarantine.

Available Models:

DS-2TP21B-6AVF/W





















Specifications

Thermal Module Image Sensor Uncooled focal plane arrays Resolution 25 Hz; 160 x 120 Pixel Pixe	<u>Specifications</u>	
Thermal Module Image Sensor Uncooled focat plane arrays Resolution 25 Hz: 160 × 120 Pixel Pitch 17 Jm Response Waveban 8 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm The 14 Jm to 14 Jm Normal Waveban 8 Jm to 14 Jm The		DS-2TP21B-6AVF/W
Image Sensor Uncooled focal plane arrays Resolution 25 Hz : 160 × 120 Response Waveband 8 µm to 14 µm Response Waveband 8 µm to 14 µm NETD < 40 mk (@ 25° C, F#=1.0) Field of View 25° × 18.7° Focal Length 6.2 mm (manual focus) Field view 25° × 18.7° Focal Length 6.2 mm (manual focus) Field view 25° × 18.7° Focal Length 7.1 Optical Module Picture Resolution Configurable: 2 MP, 5 MP, 8 MP Video Resolution 640 × 480 Monitor 840 × 480 with a state of the configurable: 2 MP, 5 MP, 8 MP Video Resolution 640 × 480 Monitor 840 × 480 with a state of the configurable: 1 MP, 1 MP, 1 MP Palettes Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal: 1x, 2x, 4x Thermal/Optical Thermal view in optical view Fusion Supports thermal view and optical view Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F185° to 45° C) Accuracy ±0.9° F1£0.5° C) Battery Battery Operating Time Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Bull-in-in memory module 116 681 Photo Thermal/Optical/fusion image Video Thermal/Optical/fusion image Wi-Fi Supported Language English Generat Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Workland Temperature (155° C)	Thermal Module	
Resoution 25 Hz: 160 x 120 Pixel Pitch 17 Jm Response Waveband 8 Jm to 14 Jm NETO 40 mk (@ 25° C, F#=1.0) Field of View 25° x 18.7° Focal Length 6.2 mm (manual focus) IFOV 2.74 mrad Aperture f7/1.1 Optical Module Picture Resolution Configurable: 2 MP, 5 MP, 8 MP Video Resolution 640 x 480 Monitor 640 x 480 resolution 3.5° LCD touch display Paletters Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal-Optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F 130° to 45° C) Accuracy ±0.9° F [±0.5° C] Battery Battery Type Dismountable and rechargeable II-ion battery Battery Operating Time Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off House in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module 1166 BP Photo Thermal/optical/fusion image Video Thermal/Optical/fusi		Ilincooled focal plane arrays
Response Waveband & Jum to 14 µm NETD < 40 mk (@ 25° C, F# = 1.0) Field of View 25° × 18.7° Focal Length 6.2 mm Imanual focus! IFOV 2.74 mrad Aperture f/1.1 Optical Module Picture Resolution Configurable: 2 MP, 5 MP, 8 MP Video Resolution 640 × 480 Monitor 640		
Response Waveband 8 Jum to 14 Jum NETD 40 mk (© 25° C, F#=1.0) Field of View 25° x 18 (© 25° C, F#=1.0) Field of View 25° x 18 (© 25° C, F#=1.0) Field of View 25° x 18 (© 25° C, F#=1.0) Field of View 25° x 18 (© 25° C, F#=1.0) Frozel Length 6.2 mm (manual focus) Froy 2.74 mrad Aperture 7/1.1 Optical Module Picture Resolution Configurable: 2 Mp, 5 Mp, 8 Mp Video Resolution 640 x 480 resolution 3.5° LCD touch display Palettes Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal/optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Naximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy 40.9° F (15.05° C) Battery Battery Type Battery Operating Time Storage Buitt-in memory module [16 GB] Photo Thermal/Optical/fusion image Video Thermal/Optical/f		
NETD		
Field of View 25° x 18.7° Focal Length 6.2 mm (manual focus) IFOV 2.74 mrad Aperture J.1. Optical Module Picture Resolution Configurable: 2 MP, 5 MP, 8 MP Video Resolution 640 x 480 resolution 640 x 480 Monitor 640 x 480 resolution 3.5° LC0 touch display Palettes Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal/Optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view in optical view combined Record Video Supports on-board video recording Thermagraphy Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 11.3° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Dismountable and rechargeable li-ion battery Battery Operating Time 5 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Video Thermal/Optical/fusion image Video Thermal/Optical/fusion image Fax Comment Supported Voice Temperature Sor to S5° F (15° to S5° C)	NETD.	∠4∩ mk (
Focal Length 6.2 mm [manual focus] IFOV 2.74 mrad Aperture f/1.1 Optical Module Picture Resolution Configurable: 2 MP, 5 MP, 8 MP Video Resolution 640 × 480 resolution 3.5" LCD touch display Palettes Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display Digital Zoom Thermat: 1x, 2x, 4x Thermal/Optical Thermal/optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view and optical view Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86" to 113" F (30" to 45" C) Battery Battery Type Dismountable and rechargeable II-ion battery Battery Operating Time Storage Built-in memory module [16 68] Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Terrace Voice (15° to 55" c) (15° to 35" c)	Field of View	25° × 18 7°
IFOV 2.74 mrad Aperture f/1.1		
Aperture f/1.1 Optical Module Picture Resolution 640 × 480 resolution 3.5° LCD touch display Palettes Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal/optical/Tusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Battery Operating Time 5 to 50° In original temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Voice Comment Supported Voice Comment Supported Voice Comment Supported Power Consumption Maximum 4.5 W Hardware Interface Power 59° to 95° F (155° to 35° C)	IFOV	2.74 mrad
Picture Resolution Configurable: 2 MP, 5 MP, 8 MP Video Resolution 640 × 480 resolution 3.5° LCD touch display Palettes Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display Digital Zoom Thermal 1x, 2x, 4x Thermal/Optical Thermal/optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view and optical view combined Record Video Record Video Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Dismountable and rechargeable li-ion battery Battery Operating Time Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Language English Generat Power 5 VUC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type - C interface Working Temperature Syb to 5° F (15° to 35° C)		
Video Resolution 640 × 480 Monitor 640 × 480 resolution 3.5° LCD touch display Palettes Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal/optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86* to 11.3° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Battery Operating Time Storage Built-in memory module (16 GB) Photo Video Thermal/optical/fusion image Wideo Thermal/optical/fusion image Wideo Thermal/optical/fusion image Text Comment Supported Voice Comment Supported Language English General Power 5 VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type- C interface Working Temperature S9° to 35° C)		
Video Resolution 640 × 480 Monitor 640 × 480 resolution 3.5° LCD touch display Palettes Black hot, white hot, red hot, rainbow, ironbow, fusion, rain Image Display	Picture Resolution	Configurable: 2 MP, 5 MP, 8 MP
Palettes Black hot, white hot, red hot, rainbow, fusion, rain Image Display Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal/optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view combined Record Video Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F [30° to 45° C) Accuracy ±0.9° F [±0.5° C] Battery Battery Type Battery Operating Time 5 Hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 Hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module [16 GB] Photo Thermal/optical/fusion image Wi-Fi Supported Voice Comment Supported Voice Comment Supported Language English Power S VOIC/2 A Power Consumption Maximum 4.5 W Hardware Interface Working Temperature S9° to 95° F [15° to 35° C)	Video Resolution	640 × 480
Palettes Black hot, white hot, red hot, rainbow, fusion, rain Image Display Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal/optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view combined Record Video Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F [30° to 45° C) Accuracy ±0.9° F [±0.5° C] Battery Battery Type Battery Operating Time 5 Hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 Hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module [16 GB] Photo Thermal/optical/fusion image Wi-Fi Supported Voice Comment Supported Voice Comment Supported Language English Power S VOIC/2 A Power Consumption Maximum 4.5 W Hardware Interface Working Temperature S9° to 95° F [15° to 35° C)	Monitor	640 × 480 resolution 3.5" LCD touch display
Digital Zoom Thermal: 1x, 2x, 4x Thermal/Optical Thermal/Optical Thermal Optical Vision image/picture-in-picture Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Dismountable and rechargeable li-ion battery Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module 116 GB] Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Voice Comment Supported Language English Power 5 VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Working Temperature 59° to 95° F (15° to 35° C)		
Thermal/Optical Thermal/optical/fusion image/picture-in-picture Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view and optical view combined Record Video Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Dismountable and rechargeable li-ion battery Battery Operating Time Storage Photo Thermal/optical/fusion image Photo Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Voice Comment Supported Language English Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (150° to 35° C)		
Picture-in-Picture Supports thermal view in optical view Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Dismountable and rechargeable li-ion battery Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Voice Comment Supported Language English Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)		
Fusion Supports thermal view and optical view combined Record Video Supports on-board video recording Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy ±0,5° F (±0.5° C) Battery Battery Type Battery Operating Time Storage Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Language English General Power Consumption Maximum 4.5 W Hardware Interface Working Temperature Sy* to 45° C) Accuracy ±0,5° C) Battery Type Simountable and rechargeable li-ion battery Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Built-in memory module [16 68] Thermal/optical/fusion image Wi-Fi Supported Supported Supported Hardware Interface Working Temperature Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Thermal/Optical	Thermal/optical/fusion image/picture-in-picture
Record Video Thermography Rules Range 86° to 113° F [30° to 45° C] Accuracy ±0.9° F [±0.5° C] Battery Battery Type Dismountable and rechargeable li-ion battery Storage Built-in memory module [16 6B] Photo Video Thermal/optical/fusion image Wi-Fi Viole Comment Voice Comment Voice Comment Voice Comment Supported Language Figilish Power Consumption Maximum 4.5 W Hardware Interface Working Temperature Voice Supportation Rules Maximum temperature; center temperature; custom point/line/area thermography Remography Re	Picture-in-Picture	Supports thermal view in optical view
Thermography Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Battery Operating Time Battery Operating Time Storage Photo Thermal/optical/fusion image Video Wi-Fi Supported Text Comment Voice Comment Voice Comment Language General Power Consumption Maximum 4.5 W Hardware Interface Working Temperature Working Temperature Sy to 95° F (15° to 35° C)	Fusion	Supports thermal view and optical view combined
Rules Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography Range 86° to 113° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Dismountable and rechargeable li-ion battery Battery Operating Time Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power S VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature; center temperature; center temperature; custom point/line/area thermography and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on supplement light on Supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Voice Comment Supported Vo		
Range 86° to 113° F (30° to 45° C) Accuracy ±0.9° F (±0.5° C) Battery Battery Type Dismountable and rechargeable li-ion battery Battery Operating Time 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on 8 Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power SVDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)		
Accuracy ±0.9° F (±0.5° C) Battery Battery Type Dismountable and rechargeable li-ion battery Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power S VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Rules	Maximum temperature; minimum temperature; center temperature; custom point/line/area thermography
Battery Type Dismountable and rechargeable li-ion battery Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Supported Supported Supported Supported Language English English English Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Range	86° to 113° t 30° to 45° C)
Battery Type Battery Operating Time Battery Operating Time Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Wi-Fi Voice Comment Language Fogerat Power Consumption Power Consumption Battery Type Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Thermal/optical/fusion image Wi-Fi Supported Supported Supported Voice Comment Supported Fogerat Power S VDC/2 A Power Consumption Hardware Interface Working Temperature S9° to 95° F (15° to 35° C)		
Battery Operating Time 5 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature So Total Comment Supported Shours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light off 4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage And Supplement light on Herdward Supplement light on Storage And Supplement light on Herdward Supplement light on Herdward Supplement light on Storage And Supplement light on Herdward Supplement light on Herdward Supplement light on Storage And Supplement light on Herdward Supplement light on Her		
4 hours in normal temperature, with Wi-Fi, Bluetooth, and supplement light on Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	7 71	E hours in normal tamparature, with Wi. Fi. Divatagth, and aupplement light off
Storage Built-in memory module (16 GB) Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power S VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Battery Operating Time	3 hours in normal temperature, with Wi-Fi, bluetouth, and supplement light on
Photo Thermal/optical/fusion image Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power S VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Storage	Anide in normal cemperature, with wirth, bue tooth, and supplement light on
Video Thermal/optical/fusion image Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power S VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Photo	Thermal /ontical /fusion image
Wi-Fi Supported Text Comment Supported Voice Comment Supported Language English General Power 5 VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Video	Thermal/ontical/fusion image
Text Comment Supported Voice Comment Supported Language English General Power 5 VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Wi-Fi	Supported
Voice Comment Supported Language English General Power S VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)		
Language English General Power 5 VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)		
General Power 5 VDC/2 A Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)		
Power Consumption Maximum 4.5 W Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)		
Hardware Interface Type-C interface Working Temperature 59° to 95° F (15° to 35° C)	Power	5 VDC/2 A
Working Temperature 59° to 95° F (15° to 35° C)		
Working Temperature 59° to 95° F (15° to 35° C) Protection Level IP54		
Protection Level IP54	Working Temperature	59° to 95° F (15° to 35° C)
Drop Test Height 6.56 ft (2 m)		
Dimension 9.6" \times 3.9" \times 4.1" (244 mm \times 100 mm \times 104 mm)	Dimension	9.6" × 3.9" × 4.1" [244 mm × 100 mm × 104 mm]
Weight With battery: 1.44 lb (653 g) Without battery: 1.13 lb (511 g)	Weight	With battery: 1.44 lb [653 g]
Without battery: 1.13 lb (511 g)		Witnout battery: 1.13 ib (511 g)

Dimensions







