INFINITEPIXELS

IPXT23D-MWV1

HD-TVI 1080P MOTORIZED Varifocal IR Outdoor Dome

Features

- HD1080P Video Output
- MOTORIZED
- True WDR, 120 dB, True Day/Night
- 2.8 – 12mm vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 120 ft IR distance
- IP66 weatherproof & IK10 Vandal Proof
- Up the Coax(via coaxial cable)
- Dual Voltage 12VDC/24VAC

Specification

Image Sensor	1 / 3” Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25(1/30) s to 1/50,000 s
Lens	2.8-12mm @ F1.4, Angle of view: 92° – 32°
Angle Adjustment	Pan: 0 – 355°, Tilt: 0 – 80°
Motorized	YES
Day & Night	ICR
Wide dynamic range	True WDR, 120 dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature	-20 °C – 60 °C (-4 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24 VAC (12 VDC: Max. 4.5W ; 24 VAC: Max. 6.5W)
Ratings	IP66, IK10
IR Range	Up to 120 ft
Dimensions	ϕ145.3 × 124.2 mm (ϕ5.72” × 4.89”)
Weight	880 g (1.95 lb)

Dimension