

SDV-HUB

Switch Digital Video Hub

Key Features

- » Communicates with up to 4 tuning adapters
- » Supports up to 24 Switch Digital Services (programs)
- » Supports Tuning Resolver Interface specification



Product Overview

The **SDV-HUB** is a 1RU device made to support up to 4 third-party tuning adapters. Each tuning adapter can support up to 6 switch digital services for a total of 24 programs in a custom channel lineup.

The SDV-HUB connects to the NXG Master Controller module via the GbE RJ45 port, providing a communication link to the NXG CableCARD® module. Switch Digital Programs for viewing can be selected in the NXG CableCARD® module user interface.

Ordering Information

Model	Stock #	Description
SDV-HUB	6744	Switch Digital Video Hub

SDV-HUB

Switch Digital Video Hub

Specifications

Input/Output		General	
Connectors:	1x RJ45 (10/100/1000 Base-T) 2x USB 2.0 2x USB 3.0	Dimensions (W x D x H):	19.0 x 10.0 x 1.75 in. (483 x 254 x 44 mm)
IP:	1 GbE - NXG Master Controller Module	Power (External Power Supply):	100-240 VAC Input 12V DC @ 3.0A Output
Monitoring & Control		Power Consumption:	5 W
Front Panel:	1x Power LED 1x Status LED 4x Active LEDs	Weight:	3.0 lbs (1.36 kg)
		Operating Temp:	32 to 122 °F (0 to 50 °C)
		Storage Temp:	-13 to 158 °F (-25 to 70 °C)
		Operating Humidity:	0 to 95% RH @ 35 °C max, non-condensation

Switch Digital Video Hub Application

