



**TRIVIEW**

# Preliminary Spec Sheet

20" Premium Series

Closed Circuit TV Monitor

## MODEL TLM-2001

<b>Panel Type</b>	20.1 inch
<b>Viewable Size</b>	408mm (H) x 306mm(V)
<b>Dot Pitch</b>	0.51mm x 0.51mm
<b>View Angle (h/v)</b>	-80°, +80°/-60°, +80°
<b>Contrast Ratio</b>	700:1
<b>Brightness</b>	450 cd/m <sup>2</sup>
<b>Resolution</b>	800 x 600
<b>Response Time</b>	16ms (tr:4ms, tf:12ms)
<b>Display Colors</b>	16.2 million
<b>Control key define</b>	Channel, Menu, Up, Down, Left, Right, Power
<b>Power Supply</b>	
<b>Input-Voltage</b>	100~240VAC
<b>Consumption</b>	<55W
<b>VIDEO</b>	
<b>Input</b>	Composite video, connector: 2 BNCS-video, connector: 1 mini-din 4 pin Level: 1.0Vp-p / 75Ω
<b>Output</b>	2 BNC connector for CVBS loop-through output
<b>OSD</b>	Contrast, Brightness, Color, Tint, Language, OSD setting, Color Temperature select, Volume, PIP, Recall, Exit
<b>System</b>	
<b>Compatibility</b>	Scanning Frequency NTSC : 15750Hz ± 500Hz / 60Hz, PAL : 15625Hz ± 500Hz / 50Hz
<b>Analog VGA</b>	
<b>Input</b>	Analog RGB: 0.707Vp-p / 75Ω, Connector: DVH (with converting cable)
<b>OSD</b>	OSD Contrast, Brightness, Phase, Clock, H Position, V Position, Auto Adjust, OSD setting, Color Temperature select, Volume, PIP, Recall, Exit
<b>Plug &amp; Play</b>	DDC2B
<b>power Management</b>	VESA DPMS
<b>Support Timing</b>	VESA VGA / SVGA / XGA
<b>Audio</b>	
<b>Input</b>	Connector: 2 x RCA jack (L+R) Level: 1.0Vp-p / 1 KHz
<b>Output</b>	Connector: 2 x RCA jack (L+R)
<b>Speaker</b>	1W x 2 embedded
<b>Dimensions</b>	18.5"(w) x 15.0"(h) x 4.3"(d) 461mm(w) x 380.5mm(h) x 110mm (d)
<b>Additional benefits</b>	3D comb filter De-interlaced PIP/VOV RoHS compliant